

COAXIALES | 75 Ω

Denominación <i>Item</i>	Coaxial RG-59 PESADO 98 % 75Ω
Artículo <i>Code</i>	CL807

	Información Técnica		Technical Information	
Conductor Interno <i>Inner Conductor</i>	CU 0.60 mm		CU 0.60 mm	
Aislación <i>Insulation Material</i>	PE Ø 3.7 mm		PE Ø 3.7 mm	
Blindaje <i>Shield</i>	Malla de CU 98 %		Braid CU 98 %	
2° Blindaje <i>2° Shield</i>				
Vaina <i>Jacket</i>	PVC Ø 6.0 mm		PVC Ø 6.0 mm	
Peso <i>Weight</i>	45 Kg/Km		45 Kg/Km	
Resistencia Conductor Máxima <i>Characteristic Impedance</i>	62 Ω/Km		62 Ω/Km	
Capacidad Nominal <i>Capacitance</i>	69 pf/mt		69 pf/mt	
Velocidad de Propagación <i>Propagation Velocity</i>	66 %		66 %	
Atenuación Nominal <i>Attenuation</i>	Frecuencia Mhz	dB/100 mts	Frequency Mhz	dB/100 mts
	50	8.6	50	8.6
	100	11.0	100	11.0
	200	16.2	200	16.2
	400	23.4	400	23.4
	700	31.0	700	31.0
	1000	40.0	1000	40.0

Referencias:

Cu-Ag: Cobre Plateado | Cu-Sn: Cobre Estañado | CW: Acero Cobre | PE: Polietileno Sólido | Al: Aluminio PEC: Polietileno Celular | HFLS: Termoplástico, lib re de halógenos y baja emisión de humos.

References:

Cu-Ag: Silver Copper | Cu-Sn: Tin Copper | CW: Steel Coated Copper | PE: Solid Polyethylene | Al: Aluminium PEC: Cell Polyethylene | HFLS: Thermoplastic Halogen-free and low smoke emission.